



XT 3.78 H

PORTABLE POWER

Water Pumps Range SPECIALIST AQUALINE

PRODUCT ADVANTAGES

- HONDA Professional Engine
- Easy acces to the turbine (without tools)
- Automatic priming
- Resistant pump-barrel
- Offeres accessories

Range SPECIALIST AQUALINE

High performance under extreme conditions.



XT 3.78 H

WATER PUMP SPECIFICATIONS

Range	SPECIALIST AQUALINE
Type liquid	Extremely heavily sedimented water pump
Suction diameter [mm]	76
Backflow diameter (mm)	76
Outflow maximum (L/min)	1340
Outflow maximum (m3/h)	80.40
Lifting height (m)	27
Suction height (m)	8
Granulometry (mm)	27
Automatic priming	Yes
Fuel	Petrol
Tank (L)	5.30
75% cons. (l/h) *	2
75% Autonomy (h) *	2.70
Sound power level guaranteed LwA dB(A)	110
Acoustic pressure level @1m in dB(A)	94
Acoustic pressure level @7m in dB(A)	80

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX240
Distribution	O.H.V.
Start	Starter
Low Oil pressure shutdown	Oui
Displacement (cm3)	242
Oil capacity (L)	1.10

DIMENSIONS AND WEIGHT

Lenght (cm)	69
Width (cm)	48.50
Height (cm)	53.20
Dry Weight (kg)	58

PACKAGING

Packaging type	Box
Length (cm)	72
Width (cm)	52
Height (cm)	58
Weight (kg)	68.50
Pallet type	120/80
Number of box by pallet	4
Pallet height (cm)	129
weight of the packaged Pallet (kg)	284



ACCESSORIES SUPPLIED



Inlet filter
Screw-on connectors



Circlips
User and maintenance manual

OPTIONS



RHO	RHO	Cover for SDMO 's generating sets, welding sets and water pumps
R12	R12	Piping kit for 3 water pumps made up of 5 m suction + 25 m lift.